

NEW

# S4M

MEET NEW  
CAR REFINISH BRAND  
FROM SERBIA



Helios Srbija a.d.  
Radovana Grkovića 24  
32300 Gornji Milanovac, Srbija  
T: +381 32 771 007  
E: info@helios.rs  
www.helios.rs

Member of HELIOS.



## S4M ANTIGRAVEL

One-component coating based on modified rubber for the protection of sills and wheel arches against stone chipping.

- Resistant to salt, moisture, oil and petrol.
- Possibility of over-coating immediately after drying
- Shades: grey, white, black
- Compliant with VOC regulations (2004/42/II B(e)(840) 420). The EU VOC limit value for this type of product (category II B (e)) in the form ready for application is 840 g/l. The VOC of this ready-to-use product amounts to 420 g/l.

- **Packaging:**  
S4M ANTIGRAVEL 1 KG (in a cardboard box 6 x 1 KG)



## S4M ANTICORROSIVE PRIMER

One-component alkyd primer that provides good anti-corrosion protection of metals (vehicle bodies and other metal parts). It is characterized by extremely fast drying (20-25 min at 20 °C).

- Easy to apply and fast drying (20-30 min at 20 °C).
- No sanding required.
- Shade: grey

- **Packaging:**  
S4M ANTICORROSIVE PRIMER 0,75 KG (in a cardboard box 6 x 0,75 KG)



## S4M 5:1 2K HS PRIMER FILLER

Two-component acrylic quick-drying Primer Filler with good anticorrosive properties. It is also characterized by good sanding properties. Can be used as a filler (applied as a thin layer) or as a Primer Filler (applied in a thicker layer).

- It is complete in set with S4M 2K HS PRIMER FILLER HARDENER (temperature by application from +18 °C to +27 °C).
- Volume mixing ratio: 5:1 (dilution 25-30 %)
- Shade: grey
- Compliant with VOC regulations (2004/42/II B (c) (540) 520). The EU VOC limit value for this type of product (category II B (c)) in the form ready for application is 540 g/l. The VOC of this ready-to-use product amounts to 530 g/l.

- **Packaging:**  
S4M 5:1 2K HS PRIMER FILLER 0,75 L (in a cardboard box 6 x 0,75 L)  
S4M 2K HS PRIMER FILLER HARDENER 0,15 L (in a cardboard box 6 x 0,15 L)



## S4M 2:1 2K CLEARCOAT AS

Two-component acrylic clearcoat as the final layer in two layer system for protection of the body of personal vehicles, buses, trucks and other vehicles). It is characterized by excellent application and vertical stability. It offers a good and smooth finish with a high level of gloss.

- Used in combination with S4M 2K CLEARCOAT HARDENER (temperature by application from +18 °C to +27 °C).
- Mixing volume ratio: 2:1 (without the addition of thinner. The product is ready for application after mixing with hardener).
- Short drying time
- High final hardness of the coating
- Compliant with VOC regulations (2004/42/II B (e) (840) 550). The EU VOC limit value for this type of product (category II B (e)) in the form ready for application is 840 g/l. The VOC of this ready-to-use product amounts to 550 g/l.

- **Packaging:**  
S4M 2:1 2K CLEARCOAT AS 1L (in a cardboard box 6 x 1 L)  
S4M 2:1 2K CLEARCOAT AS 5 L (in a cardboard box 4 x 5 L)  
S4M 2K CLEARCOAT HARDENER 0,5 L (in a cardboard box 6 x 0,5 L)  
S4M 2K CLEARCOAT HARDENER 2,5 L (in a cardboard box 4 x 2,5 L)



## S4M UNIVERSAL THINNER

Universal thinner that can be used for dilution of many products (temperatures of application from +18 °C to +27 °C).

- **Packaging:**  
S4M UNIVERSAL THINNER 1 L (in a cardboard box 12 x 1 L)

